

## FGY-X系列吸顶灯(LED)

FGY-X Series Ceiling Light Fittings (LED)



Waterproof



Dustproof



Corrosionproof

GB

IEC

EN

GOST

### 型号规格含义 Nomenclature



### 产品特点 Product features

- ◆ 铝合金壳体;
- ◆ 贴片式LED光源;
- ◆ PC透明罩;
- ◆ 可根据要求增加应急或人体感应功能。
- ◆ Aluminium alloy enclosure.
- ◆ SMD LED strip light source.
- ◆ PC transparent cover.
- ◆ Emergency or human body sensing functions may be added as requested.

### 产品规格 Product specifications

型号规格 Model Specifications	灯具功率 Lamp power	灯具光通量 Lamp luminous flux	色温 Color temperature	显色指数 CRI	壳体类型 Enclosure type	重量 Weight
FGY-X10	10W	≥800lm	5700K	Ra≥80	I	0.85kg
FGY-X20	20W	≥1600lm				0.90kg
FGY-X30	30W	≥2500lm			II	1.45kg
FGY-X40	40W	≥3700lm				1.50kg

### 产品描述 Product description

执行标准：中国GB标准 / 国际IEC标准 / 欧盟EN标准

额定电压：220V~240V AC 50/60Hz

引入口装置：I型：PG9(Φ4mm~Φ8mm)

II型：M15×2(Φ4mm~Φ8mm)

防护等级：IP65

Executive standards: Chinese GB standards / International IEC standards / European EN standards

Rated voltage: 220V~240V AC 50/60Hz



Cable gland: Type I : PG9(Φ4mm~Φ8mm)

Type II: M15×2(Φ4mm~Φ8mm)


Degree of protection: IP65

### 外形尺寸

Outline dimension (mm)



10W/20W



30W/40W