

Local, Caution Spotlight Fittings BAJ52-20 Series Explosion-proof Emergency Light Fittings



- ◆ Explosion protection to
 - CENELEC
 - IEC
 - NEC
- ◆ Can be used in
 - Zone 1 and Zone 2
 - Class I, Zone 1 and Zone 2
 - Class I, Division 1, Groups C, D
- ◆ Enclosure in Copper-free Aluminium Alloy, powder coated surface, yellow (RAL1021).
- ◆ Lighting angle can be adjusted.
- ◆ Low-power halogen tungsten lamps, with reflector to increase lighting intensity.
- ◆ Emergency device with Ni-MH batteries, charging automatically; when power supply is cut off, the emergency device starts to work; with overcharge and overdischarge protection.
- ◆ Toughened glass cover resistant to temperature changes.

Local, Caution Spotlight Fittings

BAJ52-20 Series Explosion-proof Emergency Light Fittings

Technical data

Explosion-proof emergency light fittings BAJ52-20

Explosion protection

Global (IECEX)	IECEX CQM 08. 0001
Gas	Ex d IIB T4
Europe (ATEX)	LCIE 07 ATEX 6086
Gas	⊕ II 2 G Ex d IIB T4
Certificates	IECEX; ATEX
Conformity to standards	EN 60079-0, EN 60079-1 IEC 60079-0, IEC 60079-1

Material

Enclosure	Copper-free Aluminium Alloy, powder coated surface, yellow (RAL1021)
Exposed fastener	Stainless steel

Rated voltage

220~240V AC 50/60Hz

Lamp

Available lamp	Halogen tungsten lamp (LED on request)
Lamp power (W)	2×10W (LED lamp power: 2×1W)
Emergency time	90min
Rated luminous flux	Halogen tungsten lamp: 2×100lm (LED lamp: 2×90lm)

Battery

Description	Ni-MH battery
Rated capacity	6Ah
Rated voltage	6V
Charging current	300mA
Discharging current	1000mA
Charging time	24h

Degree of protection

IP65

Ambient temperature

-20°C~+55°C

Terminal

3×1.5~2.5mm² (L+N+PE)

Cable entries

2×M25×1.5 plugs

Cable gland (optional)

DQM-II (Ex d) or DQM-III (Ex d) is recommended. Please see P6/24~39.

Weight

5.05kg



Dimension drawings (all dimensions in mm) - subject to alteration

